

RIGGER LIFT RS60



Rigger Lift
www.riggerlift.com
P.O. BOX 376 DAVISON, MI 48423

MODEL **PS-60** SERIAL NO. **1208-RS60-006**

Basic MODEL CAPACITY **60000** LBS. @ **24** "LOAD CTR

BASE CHASSIS less forks	44180	LBS.	Wheelbase	160 IN
BASE CHASSIS w/ forks	47980	LBS.	Tread Width	
BASE CHASSIS STEER-AXLE	15260	LBS.		
TOTAL COUNTERWEIGHTS	11680	LBS.		
TOTAL STEER-AXLE	26940	LBS.		
TOTAL CHASSIS	59660	LBS.		

1510-001

WORKS & ATTACHMENTS

MAX. Lift Height **96 IN**

MAX. Lowered Height **118 IN**

Rigger Lift
www.riggerlift.com
P.O. BOX 376 DAVISON, MI 48423

BASE CHASSIS CHASSIS CAPACITIES with FORKS

1 COUNTERWEIGHT	35686	LBS. @ 24	"LOAD CTR
2 COUNTERWEIGHTS	49156	LBS. @ 24	"LOAD CTR
3 COUNTERWEIGHTS	60000	LBS. @ 24	"LOAD CTR
4 COUNTERWEIGHTS		LBS. @	"LOAD CTR
5 COUNTERWEIGHTS		LBS. @	"LOAD CTR
6 COUNTERWEIGHTS		LBS. @	"LOAD CTR

Operator must follow standard operating procedures for forklift operation. The above capacity ratings are for evenly distributed loads with the mast in a vertical position. Maximum speed of 1 MPH. It is the operator's responsibility to read and understand all information on this specification plate.

BOOM ATTACHMENT

MODEL **BM-80**

SERIAL NO. **0209-BM80-007**

25000 lbs. @ 85 in. Load Center

42585 lbs. @ 28 in. Load Center

50046 lbs. @ 16 in. Load Center

Max. Hyd. Pressure **2000**

Weight **8500**

NOTE: THE WEIGHTS OF ALL LOAD HANDLING DEVICES ARE CONSIDERED PART OF THE LOAD TO BE LIFTED AND MUST BE SUBTRACTED FROM THE ABOVE CAPACITIES.

CAPACITIES OF TRUCK AND ATTACHMENT MAY BE LESS THAN CAPACITIES SHOWN ON ATTACHMENT. CONSULT TRUCK SPEC PLATE FOR FURTHER INFORMATION ON CAPACITIES AND LOAD CENTERS.

SPEED MUST NOT EXCEED 1 MPH

NOTE: LOAD CAPACITIES ARE BASED ON STRUCTURAL STRENGTH ONLY, NOT TIPPING.

RIGGER LIFT MFG. INC.
P.O. BOX 376
DAVISON, MI 48423
110-658-2127 - www.riggerlift.com

1510-01